

SPECIFICATION

Recessed Toilet Paper Holder with round bezel for chase mounting shall hold one (1) standard toilet paper roll and shall be fabricated of alloy 18-8 stainless steel, type 304, N° 14 gauge. Beveled trim shall have N° 4 satin finish. Back mounting plate shall be fabricated of N° 11 gauge dieformed galvanized steel. Hardware mounting kit (supplied) shall include two (2) 1/4"-20 threaded rods of length specified at time of order with two (2) washers and nuts each. Back of paper holder shall be provided with two (2) welded-on internally threaded anchor T-nuts to receive the two (2) 1/4"-20 threaded rods.

Recessed Toilet Paper Holder shall be Model Nº 110-A as fabricated by American Specialties Inc., 441 Saw Mill River Road, Yonkers, New York 10701-4913

INSTALLATION

For compliance with ADA Accessibility Guidelines install unit so that centerline of paper holder is 19" (483mm)minimum above finished floor (AFF) to 44"(1118mm) maximum AFF and leading edge of roll is no farther than 36"(914mm) from back wall behind commode. Recess mount paper holder into wall opening. Insert two (2) 1/4"-20 threaded rods into two (2) welded-on anchor T-nuts. Install back mounting plate over threaded rods and secure to wall with washers and nuts (supplied). The length of the rods is determined by the thickness of the wall in which the paper holder will be mounted. Specify suffix for the thickness of the wall in the following increments (e.g. 110-A-61):

Wall Thickness	<u>Suffix</u>
4 -3/4" - 6" (121mm - 152mm)	46
Over 6" (152mm) but not over 11-1/2" (292mm)	61

Rough wall opening (RWO) required is 6" (152mm) diameter

OPERATION

One roll of toilet paper is stored in the 5-1/2" (140mm) dia. x 4-1/2" (114mm) deep cylindrical holder. Toilet paper is replenished on a cycle determined by maintenance needs.

Accessory Specialties

AMERICAN DISPENSER

Desert Rau Products

WATROUS INC.

THIS MANUFACTURER RESERVES THE RIGHT TO MAKE CHANGES IN DESIGN OR DIMENSIONS WITHOUT FORMAL NOTICE