

RECESSED COMBO 3-IN-1 MODEL 64672



## **3-IN-1 PAPER TOWEL DISPENSER WITH WASTE RECEPTACLE AND AUTOMATIC ELECTRIC HAND DRYER HAS GONE HIGH-SPEED**

### **Other New American Specialties Hand Dryers**



*TURBO-Tuff™*



*Turbo-ADA™*



*TRI-Umph™*

Introducing a new 3-in-1 paper towel dispenser with waste receptacle and automatic hand dryer (model 64672) featuring the **TURBO-ADA** (model #0199). The compact high-speed hand dryer is a perfect fit for this unit. Model 64672 operates automatically using an infrared sensor, auto-resetting thermostat, dries hands in less than 15 seconds and a 60 second automatic shut off. To keep the paper towels in the waste receptacle from blowing out, a spring-loaded lid has been added. Also available for semi-recessed and surface mounting.

**ASI**<sup>®</sup> *Integrated Solutions*  
Partitions · Accessories · Lockers

**SPECIFICATIONS**

Recessed Combo 3-in-1 Paper Towel Dispenser with Waste Receptacle and Automatic Electric Hand Dryer shall hold and dispense 500 standard multi-fold or 400 standard C-fold paper towels and shall have a waste capacity of 6.8 gal (26 L). Dispensing of multi-fold or C-fold paper towels shall not require an additional adapter. Cabinet, door, dispenser and waste receptacle (WR) shall be type 304 stainless steel alloy 18-8. All exposed surfaces shall have satin finish and shall be protected during shipment by PVC film easily removable after installation. Cabinet shall be 20 gauge with a 5/8" (16) wide perimeter trim to lay flush against wall and shall have no exposed fastening devices or visible seams. Full-face door shall be 18 gauge, fabricated from one piece with no miters or seams on face and shall have 1/2" (13) square returns to the wall. Door shall be attached to cabinet body with a full length 3/16" diameter (Ø4.8) stainless steel multi-staked piano hinge and shall be held closed with two (2) tumbler locks keyed alike to other ASI washroom equipment. Towel dispensing slot shall have a fully hemmed-in rolled edge for snag-free dispensing and user safety. WR shall have piano-hinge mounted closed top with spring-hinge closed flap door and hemmed edges for safety. Structural assembly of all cabinet components shall be of welded construction. Hand Dryer shall operate automatically from IR sensor that shall activate dryer when hands are placed in sensor zone. Complete dryer specifications and warranty information is contained in the Model No. 0199 TDS. Complete dryer Owner’s Manual (OM) and Installation Guide (IG) shall be provided with unit.

UNIT SIZE: 15-3/8" W x 55-3/8" H x 7-1/2" D (391 x 1407 x 191 mm)

WALL OPENING: 14-3/32" W x 54-3/8" H x 7-1/4" D minimum (358 x 1381 x 184 mm)

MODEL	TYPE	VOLTS@ 50/60 Hz	AMPS	WATTS	DRYING TIME	COVER
64672-1	Fixed nozzles for hands	110 ~ 120	8.33	1000	Automatic, Less than 15 seconds	White
64672-2		208 ~ 240	5.2	1000		

AIR SPEED	MOTOR	H/P	RPM x 1000	FAN TYPE	AIR FLOW	HEATING ELEMENT	OUTPUT AIR TEMPERATURE
230 ft/s [157 mi/h] (70 m/s [252 km/h])	Brush Type Dual Ball Bearings with 275°F (135° C) or 203°F (95°C) auto reset circuit breaker	0.67	29	Multi Inlet Centrifugal	60 CFM (102m³/h)	325 - 450 W Nichrome wire with auto reset circuit breaker and thermostat	131° F (55° C) @ 77° F (25° C) ambient room temperature



American Specialties, Inc.  
 441 Saw Mill River Rd, Yonkers, NY 10701  
 Tel: 914.476.9000 Fax: 914.476.0688  
 E-mail: info@americanspecialties.com  
 Web: americanspecialties.com