

**EZ Fill™ Water Faucet**

Soap Dispensers

EZ Fill

MasterFormat Section 10 28 13




Scan for  
Information



**SUSTAINABILITY/LEED**

MR 4.1 (1) MR 6 (1) EQ 4.2 (1)

MR 4.2 (1) EQ 4.1 (1) EQ 4.4 (1)



**NOTE:**  
ALL DIM'S INCH [MM]  
ILLUSTRATION FOR REF ONLY AND NTS  
SEE SOAP DISPENSER CARE & MAINTENANCE  
DOCUMENT ONLINE FOR CLEANING

**PRODUCT OVERVIEW**

Matching water faucet for EZ Fill™ soap dispensing system. Constructed of Chrome Plated or Matte Black finish spout and battery or AC power operated, hands-free sensor housing.

**KEY FEATURES & SPECIFICATIONS**

- FAUCET - Matches the EZ Fill Soap Dispensers
- Cohesive Design
- Type 304 Stainless Steel - Chrome Plated or Matte Black
- Vanity Mounted
- Automatic - Battery or AC Option - "No Touch"
- Water Flow: 1.89 LPM / 0.5 GPM – SSR PCA stream

## **OPERATION & MAINTENANCE**

System shall operate each time an object is positioned within the sensing range of 1-3/16" to 3-15/16" [30 to 100]  $\pm$  3/8" [10] directly in front of the spout of the dispenser. Optional remote control unit will allow owner programming of alternate dispense amounts. See Owner's Manual for complete description of functions.

## **TECHNICAL INFORMATION / PRODUCT PROPERTIES**

Property	Value
Dimensions	N/A
Construction	Chrome Plated ABS or Matte Black ABS
Mounting	Vanity/Counter Mount
Options	1A - Battery Operation, Bright Chrome 1A-41 - Battery Operation, Matte Black 1AC - AC Operation, Bright Chrome 1AC-41 - AC Operation, Matte Black

## **INSTALLATION**

Install spout and sensor housing to vanity deck with anti-rotation kit escutcheon flange, rubber washers and basin nut (supplied) through 1-1/8" diameter [28 dia.] mounting hole and 5/32" diameter [4 dia.] adjacent hole for anti-rotation pin of escutcheon flange. Connect flex tubing from faucet head to water supply. Mount battery compartment in convenient location under vanity deck with one (1) screw. Install six (6) 'AA'-size 1.5V cells (supplied by others) in under-deck battery compartment according to polarity indication and screw lock cover. Alternatively, plug AC Adapter into GFCI power outlet located under vanity within 13.5 ft (412 cm) of battery box and plug connector into mating inline power connector. See OM & IG provided in box with unit for complete installation details.

## **WARRANTY**

One (1) Year from date of Invoice