

Sanitary Napkin Disposal with Lock - Recessed

Feminine Hygiene Vendors and Disposals

MasterFormat Section 10 28 13







Sustainability/LEED

MR 4.1 (1) MR 6 (1) EQ 4.2 (1) MR 4.2 (1) EQ 4.1 (1) EQ 4.4 (1)

13" [330] 11" [279] 1/4" [6] -- 4" [102] - 11-1/4" [286] P 6-1/2" [165] GRAPHIC SYMBOL 7-CLIP CAN RECOMMENDED MOUNTING HEIGHT 43-1/2" [851] ROUGH WALL OPENING REMOVEABLE RECEPTACLE 5-1/2" [140] 4" [102] MOUNTING HOLES 2-1/8' [54] \square 2" [51] + TYP © TUMBLER FINISHED FLOOR

NOTE: ALL DIM'S INCH [MM] ILLUSTRATION FOR REF ONLY AND NTS

PRODUCT OVERVIEW

Self-closing door is mounted to cabinet with stainless steel spring hinge. Recessed for side wall installation. Holds 1.5 gal (5.7 liters) of dry/solids waste. Includes tumbler lock for servicing. Users push door to deposit waste material. Door is self-closing. Maintenance schedule determines waste removal cycle. Unit is emptied by removing bottom waste container and inverting over collection bag. Waste container is captured by internal angle and lock to prevent inadvertent dumping , unauthorized removal and Door, flanges, waste receptacle and cabinet shall be 22 gauge type 304 stainless steel alloy 18-8.

KEY FEATURES & SPECIFICATIONS

- Disposal with Lock
- Type 304 Stainless Steel Satin Finish
- Recessed
- 1.5 gal (5.7 L) of dry/solids Waste Capacity

American Specialties, Inc. | 441 Saw Mill River Road, Yonkers, NY 10701 | (914) 476-9000 | www.americanspecialties.com

Model:#0473-1

Revision: R5 | Issued: 11/1/2021 | Revised: 1/30/2025

CSI: 10 28 13 Toilet Accessories

Page: 1 of 2



OPERATION & MAINTENANCE

Users push door to deposit waste material. Door is self-closing. Maintenance schedule determines waste removal cycle. Unit is emptied by removing bottom waste container and inverting over collection bag. Waste container is captured by internal angle and lock to prevent inadvertent dumping, unauthorized removal and

TECHNICAL INFORMATION / PRODUCT PROPERTIES

Property	Value
Dimensions	13" [330] W x 4-1/4" [108] x 17-1/4" [438]
Construction	Type 304 Stainless Steel - Satin Finish
Mounting	Recessed
Capacity	1.5 gal (5.7 L) of dry/solids Waste Capacity

INSTALLATION

Unit is mounted in wall recess using #10 self-threading screws (by others) through concealed mounting holes provided. Note top of rough wall opening is 3/4" [19] below top of unit.

Rough Wall Opening (RWO) required is 11-1/4" [268] W x 15-3/4" [400] H x 4" D minimum [102]

WARRANTY

One (1) Year from date of Invoice

American Specialties, Inc. | 441 Saw Mill River Road, Yonkers, NY 10701 | (914) 476-9000 | www.americanspecialties.com

Model: #0473-1

Revision: R5 | Issued: 11/1/2021 | Revised: 1/30/2025