

Velare™ – Stainless Steel Cabinet with Frameless Mirror, Foam Soap Dispenser and Paper Towel Dispenser Velare Soap Dispensers - 23-5/8" [600] -MasterFormat Section 10 28 13 11-13/16* [300] CENTRAL 6-3/16" [157] 5-13/32" [137] 7-7/32° [183] Scan for Information SENSORIENS OAM SOAP SPENSER NOZZLE Sustainability/LEED DETAIL A MR 4.1 (1) MR 6 (1) EQ 4.2 (1) ALL DIM'S INCH [MM] ILLUSTRATION FOR REF ONLY AND NTS MR 4.2 (1) EQ 4.1 (1) EQ 4.4 (1) SEE SOAP DISPENSER CARE & MAINTENANCE DOCUMENT ONLINE FOR CLEANING

PRODUCT OVERVIEW

ASI's Velare™ Behind the Mirror (BTM) is designed for elegance and safety in mind, concealing consumables in a cabinet made from type 304 stainless steel. The cabinet features a mirrored door with backlit icons that indicate functions provided from the bottom panel of each module. Mirror is made from 1/4" [6] thick frameless tempered glass conforming to ASTM C-1048 with pencil edges and eased corners with SS sheet intermediate stiffener and SS back plate with integral welded support mounts, hinge and lock keeper. The mirrored door is attached to the cabinet using a full width 3/16" diameter [5 dia.] concealed piano hinge and is secured shut using a tumbler lock and key. Support for mirror door is provided by twin damped gas springs to assist opening from 15° to 90° with soft-stop cushion at full open and when lowering to full closed position for locking. This wall mounted stainless steel cabinet conceals a hands-free automatic liquid soap dispenser with a 1.5 gal (6 L) capacity and paper towel dispenser with a 500 towel capacity. Mirror backlights operate on 100 - 240 VAC provided to quad (double-duplex) outlet (by others) concealed behind the cabinet into which a standard appliance power cord and AC adapters are plugged into at installation. Soap Requirements: Proper usage of this dispenser requires, that only soap within the following range for viscosity and pH may be used. Viscosity Range (mPaes or cP): 1 – 100. pH Range: 5.5 ~ 8.5 Matching filler modules (FM) are available as spacers between cabinets.

KEY FEATURES & SPECIFICATIONS

- Space saving mirror cabinet conceals a high capacity foam soap dispenser and paper towel dispenser
- Backlit icons etched into the mirror direct the user to soap dispenser and drying option
- Cabinet body is made of Type 304 Stainless Steel
- 1/4" thick tempered glass mirror has a pencil edge with a radius for safety and elegance
- Surface Mounted
- High Capacity 500 Paper Towels
- Foam Soap Dispenser 1.5 Gal (6.0 L) Capacity

441 Saw Mill River Road, Yonkers, NY American Specialties, Inc. 10701 (914)476-9000 www.americanspecialties.com Model: #0663-T Revision: R2 Issued: 11/1/2021 Revised: 5/2/2023

Page: 1 of 2

OPERATION & MAINTENANCE

Towels are self-feeding until supply is depleted from manually loaded stack. Use MFTA-2 with Z-Fold (Multi-Fold) towels, placed in towel chute with rounded lips down. Remove MFTA-2 when using C-Fold towels and store inside cabinet next to towel chute. HEPA filter is changed on cycle determined by maintenance needs for models with hand dryer. Foam type soap with a pH in range 7 ± 1.5 and viscosity range 0~100 cP (mPa•s) is refilled into 6L tank on cycles determined by maintenance needs. Towel stack is replenished on cycle determined by maintenance needs. Locked compartment prevents unauthorized access or removal. See Owner Manuals for complete details of operation.

TECHNICAL INFORMATION / PRODUCT PROPERTIES

| Property | Value |
|--------------|--|
| Dimensions | 23-5/8" x 35-7/16" x 7-9/16" [600 x 900 x 192] |
| Construction | Type 304 Stainless Steel - Satin Finish. 1/4" thick tempered glass mirror w/ radiused pencil edge. |
| Mounting | Surface Mounted |
| Options | N/A |

INSTALLATION

Mount unit on wall using twelve (12) #12 self threading, pan-head screws (by others) through two (2) concealed mounting plates into appropriate anchoring and wall reinforcements and hang unit on hooks on mounting plates. Install two (2) #12 self-threading locking screws (by others) into appropriate anchoring to prevent unit from being lifted off hanger hooks. Suggested mounting height is to position bottom of module 16" to 20" [406 to 508] above vanity top. See complete guide before starting installation.

WARRANTY

One (1) Year from date of invoice

American Specialties, Inc. | 441 Saw Mill River Road, Yonkers, NY 10701 | (914) 476-9000 | www.americanspecialties.com

Model:#0663-T

Revision: R2 Issued: 11/1/2021 Revised: 5/2/2023