

# Utility Hook Strip (5 Hooks) 46" - Surface Mounted

Custodial Accessories

MasterFormat Section 10 28 13



Scan for Information







MR 4.1 (1) MR 6 (1) EQ 4.2 (1) MR 4.2 (1) EQ 4.1 (1) EQ 4.4 (1)

46" [1168]


HOOK QTY PER SCHEDULE,
EQ SPACING ON 10" [254] CENTERS

7/32" DIA [Ø5,6]
MOUNTING
HOLES TYP

1-1/4" [32]

FQ. DISTANCE
HOLES PER SCHEDULE

EQ. DISTANCE
HOLES PER SCHEDULE



NOTE:
ALL DIM'S INCH [MM]
ILLUSTRATION FOR REF ONLY AND NTS

#### **PRODUCT OVERVIEW**

Fabricated of type 304 stainless steel with satin finish, this strip is 4" [100] high with edges returning 1/2" [13] to the wall. With 5 hooks 46" [1168].

## KEY FEATURES & SPECIFICATIONS

- With 5 Hooks
- 20 gauge type 304 Stainless Steel Satin Finish
- Surface Mounted
- 46" [1168] Length

American Specialties, Inc. | 441 Saw Mill River Road, Yonkers, NY 10701 | (914) 476-9000 | www.americanspecialties.com

Model:#1307-5

Revision: R2 Issued: 11/1/2021 Revised: 5/30/2023

CSI: 10 28 13 Toilet Accessories



Rags and towels are placed on the hooks as needed.

# TECHNICAL INFORMATION / PRODUCT PROPERTIES

Property	Value
Dimensions	46" [1168] W x 9-3/4" [248] H x 2-3/16" [56] D
Construction	Type 304 Stainless Steel - Satin Finish
Mounting	Surface Mounted
Capacity	5 Hooks

### INSTALLATION

For general utility mount unit 72" [1829] Above Finished Floor (AFF) from centerline of hook strip mounting holes. Surface mount unit to wall with #10 self-threading pan head screws (by others) through straight mounting holes in strip into suitable anchors, blocking or other wall reinforcements (by others) adequate to carry intended loads on fully utilized hooks. For compliance with 2010 ADA Accessibility Standards install unit so that top of hook is 48" [1219] maximum AFF.

#### WARRANTY

One (1) Year from date of Invoice

American Specialties, Inc. | 441 Saw Mill River Road, Yonkers, NY 10701 | (914) 476-9000 | www.americanspecialties.com

Model:#1307-5

Revision: R2 Issued: 11/1/2021 Revised: 5/30/2023