

# Simplicity™ Collection Paper Towel Dispenser (475 Multi, 350 C-Fold) – Recessed

Paper Towel Dispensers

Simplicity

MasterFormat Section 10 28 13



Scan for Information



## Sustainability/LEED

MR 4.1 (1) MR 6 (1) EQ 4.2 (1) MR 4.2 (1) EQ 4.1 (1) EQ 4.4 (1)

4" [102] 2" [51] 12-3/4 [324] 1-1/2" [38] **TUMBLER** LOCKS STAINLESS STEEL 2-1/4' PIANO HINGE [57] 17-1/4" 1-1/2" 15-1/4" [438] [38] [387] 6-3/4" 5-3/4" 5' [171] [146] 3/16" DIA [Ø5] [127] **MOUNTING HOLES** TYP 1" [25] 1/2" [13] -

# ALL DIM'S INCH [MM] ILLUSTRATION FOR REF ONLY AND NTS

FOR CLEANING INSTRUCTIONS SEE APPROPRIATE SECTIONS IN PRODUCT CARE & MAINTENANCE BULLETIN (PCM) ON ASI WEBSITE

#### PRODUCT OVERVIEW

Well-suited for the smaller washroom with less space and traffic, this unit dispenses 350 C-fold or 475 multi-fold paper towels. Door held closed with tumbler lock. All exposed surfaces have satin finish. Towels are self-feeding until supply is depleted. Unit may be reloaded with a partial load in-place and will continue to feed properly.

## KEY FEATURES & SPECIFICATIONS

- Seamless construction, crisp lines and minimalistic design
- Concealed multi-staked hinge 3/16" diameter [Ø5]
- Type 304 Stainless Steel Satin Finish
- Recessed
- 350 C-Fold OR 475 Multi-Fold

American Specialties, Inc. | 441 Saw Mill River Road, Yonkers, NY 10701 | (914) 476-9000 | www.americanspecialties.com

Model:#6457

Revision: R1 | Issued: 11/1/2021 | Revised: 3/10/2023

CSI: 10 28 13 Toilet Accessories Page: 1 of 2



### **OPERATION & MAINTENANCE**

Towels are self-feeding until supply is depleted. Unit may be reloaded with a partial load in-place and will continue to feed, properly.

## TECHNICAL INFORMATION / PRODUCT PROPERTIES

Property	Value
Dimensions	12-3/4" [324] W x 17-1/4" [438] H x 4-1/2" [114] D
Construction	Type 304 Stainless Steel - Satin Finish Concealed multi-staked hinge - 3/16" Dia. [Ø5]
Power	N/A
Operation	Manual
Mounting	Recessed
Capacity	350 C-Fold OR 475 Multi-Fold

#### INSTALLATION

Mount unit in wall recess using #10 self-threading screws (by others) through concealed mounting holes provided. For compliance with 2010 ADA Accessibility Standars install unit so that centerline of towel dispenser slot is 48" [1219] maximum above finished floor (AFF). For general utility mount unit 42" [1067] from top of finished floor to bottom of unit. Note that top of RWO is 3/4" [19] below top of unit.

Rough Wall Opening (RWO) required is 11-1/4" [286] W x 15-3/4" [400] H x 4-1/4" [108] D minimum

#### WARRANTY

One (1) Year from date of Invoice

American Specialties, Inc.	441 Saw Mill River	Road, Yonkers, NY	10701   (914)	476-9000   www.a	mericanspecialties.com
Model: #6457			Revision: R1	Issued: 11/1/2021	Revised: 3/10/2023