

# Simplicity Collection Paper Towel Dispenser (475 Multi - 350 C-Fold) & Waste Receptacle – Recessed

Paper Towel Combination Units

Simplicity

#### MasterFormat Section 10 28 13



Scan for Information






#### Sustainability/LEED

MR 4.1 (1) EQ 4.1 (1) MR 4.2 (1) EQ 4.2 (1)

MR 6 (1) EQ 4.4 (1)



ALL DIM'S INCH [MM]

ILLUSTRATION FOR REF ONLY AND NTS

FOR CLEANING INSTRUCTIONS SEE APPROPRIATE SECTIONS IN PRODUCT CARE & MAINTENANCE BULLETIN (PCM) ON ASI WEBSITE

# **PRODUCT OVERVIEW**

Well-suited for the smaller washroom with less space and traffic, this unit dispenses 350 C-fold or 475 multi-fold paper towels. Includes 2.2 gal. (8.4 L) stainless steel waste receptacle. Door held closed with tumbler lock. All exposed surfaces have #4 satin finish. Towels are self feeding until supply is depleted. Unit will continue to feed properly when reloaded with a partial load in place. Locked door prevents unauthorized access or removal.

# KEY FEATURES & SPECIFICATIONS

- Seamless construction, crisp lines and minimalistic design
- Concealed multi-staked hinge 3/16" diameter [Ø5]
- Type 304 Stainless Steel Satin Finish
- Recessed
- 350 C-Fold or 475 Multi-Fold / 2.2 Gal. (8.4 L) Waste Capacity

American Specialties, Inc. | 441 Saw Mill River Road, Yonkers, NY 10701 | (914) 476-9000 | www.americanspecialties.com

Model:#64623 Revision: R3 Issued: 11/1/2021 Revised: 11/15/2023

CSI: 10 28 13 Toilet Accessories Page: 1 of 2



# **OPERATION & MAINTENANCE**

Towels are self-feeding until supply is depleted. Unit will continue to feed properly when reloaded with a partial load in place. Waste receptacle is emptied manually on a cycle determined by maintenance needs. Locked door prevents unauthorized access or removal.

# TECHNICAL INFORMATION / PRODUCT PROPERTIES

Property	Value
Dimensions	14-1/4" [362] W x 28" [711] H x 4-3/4" [121] D
Construction	Type 304 Stainless Steel - Satin Finish
Mounting	Recessed
Capacity	350 C-Fold or 475 Multi-Fold / 2.2 Gal. (8.4 L) Waste Capacity

#### INSTALLATION

Mount unit in wall recess with #10 self-threading screws (by others) through concealed mounting holes provided. Note that top of Rough Wall Opening is 3/4" [19] below top of unit.

Rough Wall Opening (RWO) required is 12-3/4" [324] W X 26-1/2" [673] H X 4-1/4" [108] D minimum

#### WARRANTY

One (1) Year from date of Invoice

American Specialties, Inc. | 441 Saw Mill River Road, Yonkers, NY 10701 | (914) 476-9000 | www.americanspecialties.com

Model: #64623 Revision: R3 Issued: 11/1/2021 Revised: 11/15/2023