American Specialties, Inc.

Model #7340-B

Technical Data Sheet

Robe Hook (Single) – Surface Mounted, Bright Finish Specialty Accessories MasterFormat Section 10 28 13 2" [51]--2" [51]-13/16" [20] R 3/16" [5] 7/16" [11]-REF 1-5/8" 2" 1" [25] [41] [51] REF REF V 1 – 1/2" [13] REF POST MOUNTING PLATE Scan for Information POST WELDED 2 III **TO FLANGE** ര MOUNTING-BRACKET LOCK SCREW SUSTAINABILITY/LEED MR 4.1 (1) MR 6 (1) EQ 4.2 (1) NOTE: MR 4.2 (1) EQ 4.1 (1) EQ 4.4 (1)

ALL DIM'S INCH [MM] ILLUSTRATION FOR REF ONLY AND NTS

PRODUCT OVERVIEW

Hook extends 2" [51] from wall and is suitable for a robe or clothing and small carry bags. Fabricated from stainless steel, bright finish. Model Option Notes: 7340-B - Bright Finish 7340-S - Satin Finish

Key Features & Specifications

- Single Hook
- Type 304 Stainless Steel Bright Finish
- Surface Mounted

441 Saw Mill River Road, Yonkers, NY 10701 American Specialties, Inc. (914) 476-9000 | www.americanspecialties.com Model:#7340-B Revision: R1 Issued: 11/1/2021 Revised: 3/10/2023

Page: 1 of 2

American Specialties, Inc.

Model #7340-B

Technical Data Sheet

OPERATION & **M**AINTENANCE

Hook is suitable for a robe or clothing and small carry bags.

TECHNICAL INFORMATION / PRODUCT PROPERTIES

Property	Value
Dimensions	2" [51] W x 2" [51] H x 2" [51] D
Construction	Type 304 Stainless Steel - Bright Finish
Mounting	Surface Mounted
Capacity	

INSTALLATION

Surface mount unit on door back or wall using two (2) #10 self-threading screws (by others) through holes provid-ed in mounting plate into suitable prepared mountings (by others) or other suitable mounting hardware (by others) to suit door or wall conditions. Hang post and flange assembly on mounting plate and tighten set screw to lock unit to plate. For compliance with ICC/ANSI A-117.1-2003 and 2010 ADA Accessibility Standards, install unit with top of hook 48" [1219] maximum Above Finished Floor (AFF) or 46" [1168] max AFF if side reach access over an obstruction (e.g. vanity) with reach depth greater than 10" [254] and less than 25" [635] is only provided or 44" [1118] max AFF if forward reach over an obstruction with reach depth greater than 20" [508] and less than 25" [635] is only provided. For general utility, install hook with centerline of mounting plate 68" [1727] AFF.

ADDITIONAL INFORMATION

N/A

WARRANTY

One (1) Year from date of Invoice

American Specialties, Inc.441 Saw Mill River Road, Yonkers, NY 10701(914)476-9000www.americanspecialties.comModel:#7340-BRevision: R1Issued: 11/1/2021Revised: 3/10/2023

Manufacturer reserves the right to make changes to the design, dimensions or functionality of the product without formal notice.