




**AMERICAN SPECIALTIES, INC.**  
 441 Saw Mill River Road, Yonkers, NY 10701  
 (914) 476.9000 • (914) 476.0688  
 www.americanspecialties.com

**MODEL №:** 9477

**ISSUED:** OCT 1990

**REVISED:** 16 MAR 2022

**PROFILE COLLECTION™ TOILET SEAT COVER DISPENSER - RECESSED**



**NOTE**

ALL DIM'S INCH [MM]

ILLUSTRATION FOR REF ONLY AND NTS

FOR CLEANING INSTRUCTIONS SEE APPROPRIATE SECTIONS IN PRODUCT CARE & MAINTENANCE BULLETIN (PCM) ON ASI WEBSITE

**SPECIFICATION**

Profile Collection™ Recess Mounted Toilet Seat Cover Dispenser shall hold and dispense 500 standard single or half-fold paper toilet seat covers contained in supply box. Cabinet and door shall be fabricated of type 304 stainless steel alloy 18-8. Cabinet shall be 22 gage, with a 1" [25] wide perimeter return to lay flat against wall. Full face door shall be 16 gage and shall be free of miters, welding or open seams with 15/16" [24] square horizontal returns to wall and 3/4" rounded vertical edges. Door shall be attached to the edge of unit with a full length 3/16" Dia. [Ø4,8] stainless steel multi-staked piano hinge and shall be held closed with a rimless tumbler lock keyed alike to other ASI washroom equipment. Cover dispensing slot shall have a fully deburred flat edge for snag-free dispensing and user safety. Structural assembly of cabinet and door components shall be of welded construction and shall have no exposed fasteners or welded seams. All exposed surfaces shall have satin finish.

**Recess Mounted Toilet Seat Cover Dispenser shall be Model № 9477 as manufactured by American Specialties, Inc., 441 Saw Mill River Road, Yonkers, NY 10701-4913**

**INSTALLATION**

Mount unit in wall recess using four (4) № 10 x 1-1/2" [Ø5 x 40] or length as appropriate for site conditions self-threading flat, oval or pan head screws (by others). Mounting holes are provided in side and rear walls of cabinet and are accessible through door for installation. For compliance with 2010 ADA Accessibility Standards, 2015 ABA Standards and ANSI 117.1 Standards install unit so that top of dispenser slot is 48" [1219] Maximum Above Finished Floor (AFF) if clear floor reach access is provided or 46" [1168] Max AFF if side reach over an obstruction only is provided (ie: vanity). Note that top of dispenser slot is 2-11/16" [68] below top of Rough Wall Opening.

**RWO required is 15-3/4" [400] W x 11-1/2" [292] H x 2-1/2" [64] D Min**

**OPERATION**

Covers are self-feeding until supply is depleted. Unit is manually reloaded with a full box through access door on a schedule determined by maintenance requirements.