

## **SPECIFICATION**

Soap Dish With Drain Holes shall be fabricated of stainless steel alloy 18-8, type 304. Soap dish shall be of drawn seamless construction and shall be fabricated with integral ribs. Support post shall be  $1" \times 1/2"$  (25mm x 13mm) rectangular tubing with formed mounting flange and bracket welded on end. A stainless steel setscrew shall be provided on bottom perimeter of flange to lock unit to mounting plate. Mounting plate shall be provided and shall be 18 gauge. Surface finish shall be bright or satin as chosen by option and indicated by code suffix.

## Soap Dish With Drain Holes shall be Model $N^{\rm o}$ 7320-B or $N^{\rm o}$ 7320-S of American Specialties, Inc., 441 Saw Mill River Road, Yonkers, New York 10701-4913

## **INSTALLATION**

Surface mount unit on wall using Nº10 self tapping screws (by others) through holes provided in mounting plate into suitable prepared mountings (by others) or other suitable mounting hardware (by others) to suit wall conditions. Hang post and flange assembly on mounting plate and tighten setscrew to lock unit to plate. For compliance with ICC/ANSI A-117.1-2003 and ADA Accessibility Guidelines install unit with top of soap dish 48" (1219mm) maximum above finished floor (MAX AFF) if clear floor forward reach or if clear floor side reach access only is provided or 46" (1168mm) MAX AFF if side reach access over an obstruction (e.g. vanity) with reach depth greater than 10" (254mm) and less than 25" (635mm) is only provided or 44" (1118mm) MAX AFF if forward reach over an obstruction with reach depth greater than 20" (508mm) and less than 25" (635mm) is only provided. For general utility mount unit with top of soap dish 8" to 12" (203mm to 305mm) above vanity basin.

## **OPERATION**

Soap dish has raised ribs to elevate soap slightly above dish surface to promote drying. Drain holes in bottom of dish allow excess water to drain away from soap.

AMERICAN DISPENSER

Accessory	Specialties
Accessory	Specialties

Desert Ray Products